

**MISTRAL
AUTOMATIC
WATER SOFTENERS**



Mistral

Selection guide

Selection guide



MODEL	HEIGHT	PEOPLE DAYS*	USAGE
MISTRAL 613	4L 535 mm	3	1 to 2 persons
MISTRAL 817	10T/M 640 mm	9	average household
MISTRAL 919	15M 685 mm	15	medium household - compact
MISTRAL 822	780 mm	15	medium household
MISTRAL 1023	22M 820 mm	24	larger household or small commercial

* Divide by the number in the household for the average time between regeneration at 280 ppm hardness.

Litres of softened water between regenerations

MODEL	At 200 ppm	At 300 ppm	At 350 ppm
4L MISTRAL 613	690	470	405
10T & 10M MISTRAL 817	2100	1370	1270
15M MISTRAL 919	3100	2180	1860
15M MISTRAL 822	3100	2180	1860
22M MISTRAL 1023	5250	3400	2950

Installation data

Width	275 mm	Maximum operating pressure	120 psi
Depth	440 mm	Minimum operating pressure	20 psi
Inlet	3/4" BSP female or male	Maximum water temperature	50° C
Outlet	3/4" BSP female or male	Minimum operating temperature	Protect from frost
Drain	1/2" BSP female or male		
Overflow	1/2" hose spigot		
Power	2 volt, 50 Hz, 3 amp fuse (transformer supplied)		

Call your local dealer

Morgan Water Engineering
 63 Hangar Ruding
 Watford
 Herts. WD19 5BH
 Tel: 0208 428 9310

for a quotation now